



2/2-way solenoid valve

Art. No. 192097

Type No. MVB.14.MS.24D.N.BV.10



no image available



Exemplary illustration

The Type 6281 valve is a servo-assisted diaphragm valve. A minimum differential pressure is always required for the valve to operate. Different diaphragm materials and operating principles are available to suit the respective applications. The standard brass body meets European drinking water requirements. Dezincification-resistant brass is available for other markets. The range of body materials is complemented by a stainless steel version. To reduce electrical power consumption during operation, coils with integrated kick-and-drop electronics using dual-coil technology are available. The valve can also be supplied with a manual override for easy maintenance and commissioning.

Technical data

Thread	G 1/4 IT
Operating pressure	0.2 - 16 bar
Voltage	24 V DC
Housing	brass
Valve seat	brass
Internal parts	stainless steel, PPS
Sealant	NBR
Medium temperature	-10 to 80 °C
Ambient temperature	0 to 55 °C
Protection IP	IP 65 (with connector socket fitted)
Electrical connection	pin terminal acc. to DIN EN 175301-803, type A
Max. operating pressure	16 bar
Min. medium temperature	-10 °C
Max. medium temperature	80 °C
Min. ambient temperature	0 °C
Max. ambient temperature	55 °C
Function	normally open (NO)
DN	10 mm
A	50.0 mm
B	94.1 mm

Commercial data

Customs tariff number	84818079
Country of origin	DE
eCl@ss 5.1.4	27220601
eCl@ss 9.0	27220601
UNSPSC_Code_v190501	40141605
UNSPSC_CodeDesc_v190501	Solenoid valves

DATA SHEET
Type 6281

Servo-assisted 2/2-way diaphragm valve

- Servo-assisted diaphragm valve up to DN 50
- Vibration-resistant, centrally screwed coil system
- Damped design for quiet closing
- Energy-saving double coil technology with kick and drop variant
- Explosion-proof variants



Product variants described in the data sheet may differ from the product presentation and description.

Can be combined with


Type 2518
Cable plug,
form A according to
DIN EN 175301 - 803



Type 2509
Cable plug,
form A according to
DIN EN 175301 - 803

Type description

Valve 6281 is a servo-assisted diaphragm valve. A minimum differential pressure is always required for the valve to function. Various diaphragm materials and circuit functions are available depending on the actual application. The standard brass body meets European drinking water requirements. For other markets, dezincification-resistant brass is available. The range includes a variant with a stainless steel body. To reduce electrical power consumption during operation, coils with integrated Kick-and-Drop (KD) electronics featuring double coil technology are available. The valve can be supplied with manual operation for easy maintenance and commissioning.

DTS 1000152082 EN Version: R Status: RL (released | freigegeben | valide) printed: 18.12.2024

Table of contents

1. General technical data	3
2. Circuit functions	4
3. Approvals and conformities	4
3.1. General notes	4
3.2. Conformity	4
3.3. Standards	4
3.4. Explosion protection	4
3.5. North America (USA/Canada)	5
3.6. Drinking water	5
3.7. Others	5
DNV GL classification	5
Oxygen	5
VDE – Certificate of conformity with factory surveillance	6
4. Materials	6
4.1. Bürkert resistApp	6
4.2. Material specifications	6
5. Dimensions	7
5.1. Standard version	7
5.2. ATEX/IECEx cable version	9
5.3. ATEX/IECEx terminal box version	10
5.4. Compressor relief valves	11
6. Performance specifications	12
6.1. Power consumption	12
6.2. Power consumption Kick and Drop coil	12
7. Product accessories	12
7.1. Cable glands for ATEX/IECEx terminal box	12
7.2. Special tool to turn the terminal box	13
8. Ordering information	13
8.1. Bürkert eShop	13
8.2. Bürkert product filter	13
8.3. Bürkert Product Enquiry Form	13
8.4. Ordering chart	14
Standard version with brass body	14
Standard version with stainless steel body	17
ATEX/IECEx cable version	18
ATEX/IECEx terminal box version	19
Compressor relief valve with brass body	20
8.5. Ordering chart accessories	20
Cable plug Type 2518, form A according to DIN EN 175301 - 803	20
Cable plug Type 2509, form A according to DIN EN 175301 - 803	21
Cable glands for ATEX/IECEx terminal box	21
Mounting set for DN 10	21

Type 6281

1. General technical data

Product properties	
Dimensions	Further information can be found in chapter "5. Dimensions" on page 7.
Material	
Seal	NBR, EPDM, FKM
Body	Brass acc. to DIN EN 50930 - 6, stainless steel (dezincification resistant on request)
Inner valve parts	Stainless steel, brass, plastic (PPS)
Orifice	DN 10...DN 50
Circuit function	Further information can be found in chapter "2. Circuit functions" on page 4.
Thermal insulation class of solenoid coil	Polyamide coil class B Epoxy coil class H
Performance data	
Duty cycle	100 % continuous operation
Switching time ¹⁾	Opening: 0.1...1.5 s Closing: 0.2...4 s
Electrical data	
Operating voltage	24 V/DC, 24 V/UC, 24 V/50...60 Hz, 230 V/UC, 230 V/50...60 Hz
Power consumption	Further information can be found in chapter "6. Performance specifications" on page 12.
Voltage tolerance	± 10 %
Medium data	
Operating medium	Medium that does not attack the housing and sealing materials Further information can be found in chapter "4.1. Bürkert resistApp" on page 6.
Medium temperature	
NBR	- 10 °C...+ 80 °C
EPDM	- 30 °C...+ 90 °C (with epoxy coil to + 100 °C) 0 °C...+ 60 °C (with drinking water approval according to UBA (PF36))
FKM	0 °C...+ 90 °C (with epoxy coil to + 120 °C)
Process/Port connection & communication	
Electrical connection	- Cable plug Type 2518 ▶, form A according to DIN EN 175301 - 803 Further information can be found in chapter "Cable plug Type 2518, form A according to DIN EN 175301 - 803" on page 20. - Cable plug Type 2509 ▶, form A according to DIN EN 175301 - 803 Further information can be found in chapter "Cable plug Type 2509, form A according to DIN EN 175301 - 803" on page 21.
Approvals and conformities	
Directives	CE, EAC
Degree of protection	IP65 with cable plug, cable connection and terminal box
Explosion protection	Further information can be found in chapter "3.4. Explosion protection" on page 4.
North America (USA/Canada)	Further information can be found in chapter "3.5. North America (USA/Canada)" on page 5.
Drinking water	Further information can be found in chapter "3.6. Drinking water" on page 5.
Others	Further information can be found in chapter "3.7. Others" on page 5.
Environment and installation	
Installation	As required, preferably with actuator upright
Ambient temperature	
Standard version	Max. + 55 °C
Version with kick and drop coil	Max. + 70 °C (max. 30 switching operations/min) Max. + 85 °C (max. 1 switching operation/min) Max. + 55 °C (for versions with UR/UL approval)

1.) Measurement at + 20 °C, 6 bar at the valve inlet and free outlet, opening: pressure reduction to 90 % of the difference to the flow pressure, closing: pressure build-up to 90 % of the inlet pressure



Visit product website ▶

3 | 21

Type 6281



2. Circuit functions

Symbol	Description
	Circuit function A (CF A) 2/2-way solenoid valve Servo-controlled Normally closed
	Circuit function B (CF B) 2/2-way solenoid valve Servo-controlled Normally open

3. Approvals and conformities

3.1. General notes

- The approvals and conformities listed below must be stated when making enquiries. This is the only way to ensure that the product complies with all required specifications.
- Not all available versions can be supplied with the below mentioned approvals or conformities.

3.2. Conformity

In accordance with the Declaration of Conformity, the product is compliant with the EU Directives.

3.3. Standards

The applied standards which are used to demonstrate compliance with the EU Directives are listed in the EU-Type Examination Certificate and/or the EU Declaration of Conformity.

3.4. Explosion protection

Approval	Description
	Optional: Explosion protection
	ATEX: EPS 18 ATEX 1232 X II 2G Ex mb IIC T4 Gb II 2D Ex mb IIIC T130 °C Db II 2G Ex eb mb IIC T4 Gb II 2D Ex mb tb IIIC T130 °C Db
	IECEx: IECEx EPS 18.0110 X Ex mb IIC T4 Gb Ex mb IIIC T130 °C Db Ex eb mb IIC T4 Gb Ex mb tb IIIC T130 °C Db

DTS 1000152082 EN Version: R Status: RL (released | freigegeben | valide) printed: 18.12.2024

Visit product website ►

4 | 21

Type 6281



3.5. North America (USA/Canada)

Approval	Description
	Valid for valves: UL Listed for the USA The valves are UL Listed for the USA according to: UL 429 (electrically operated valves) and UL 429A (Electrically Operated Valves for Fire Protection Service)
	Valid for coils: UL Hazardous Locations – Explosion Protection UL Listed for Hazardous Locations for USA and Canada Class I, Zone 1 Class I, Division 2, Group A, B, C and D Class II + III, Division 2, Group F and G
	Valid for valves: UL Recognized for the USA The valves are UL Recognized for the USA according to: UL 429 (electrically operated valves) and UL 429A (Electrically Operated Valves for Fire Protection Service)
	Valid for coils: UL Recognized for the USA and Canada The coils are UL Recognized for the USA and Canada according to: - UL 429 (electrically operated valves) - CAN/CSA-C22.2 No. 61010-1
	Valid for valves: CSA for Canada The valves are CSA approved for Canada according to: CSA 139 (electrically operated valves)

3.6. Drinking water

Conformity	Description
	Suitable for use in drinking water applications The materials comply with the assessment principles (UBA) for materials in contact with drinking water (TrinkwasserV). PF39: Suitable for products with a maximum temperature of 85 °C (hot water) PF36: Suitable for products with a maximum temperature of 60 °C (warm water)

3.7. Others

DNV GL classification

Approval	Description
	DNV GL classification – Ships, offshore units, and high speed and light craft The products are accepted for installation on all vessels classed by DNV GL.

Oxygen

Conformity	Description
	Optional: Suitability for oxygen (valid for the variable code NL02) The products are suitable for use with gaseous oxygen, according to the manufacturer's declaration.

Visit product website ►

5 | 21

Type 6281



VDE – Certificate of conformity with factory surveillance

Approval	Description
	Optional: Certificate of conformity with factory surveillance (VDE Testing and Certification Institute) (valid for the variable code PW01 and PW02) The electrically operated water valves are tested and certified according to: • DIN EN 60730-1 (VDE 0631-1) • EN 60730-1 • DIN EN IEC 60730-2-8 (VDE 0631-2-8) The electrically operated water valves also fulfill the requirements of: • IEC 60730-1 • IEC 60730-2-8

4. Materials

4.1. Bürkert resistApp




Bürkert resistApp – Chemical resistance chart

You want to ensure the reliability and durability of the materials in your individual application case? Verify your combination of media and materials on our website or in our resistApp.

[Start chemical resistance check](#)

4.2. Material specifications



No.	Element	Material
1	Coil	Polyamide ¹⁾ or Epoxy ²⁾
2	Stopper	Stainless steel 1.4113
3	Shading ring	Cu (brass version) Ag (stainless steel version)
4	Magnetic core	Stainless steel 1.4113
5	O-rings	NBR, FKM, EPDM
6	Core seal	NBR, FKM, EPDM
7	Spring	Stainless steel 1.4310
8	O-rings	NBR, FKM, EPDM
9	Diaphragm	NBR, FKM, EPDM
10	Diaphragm holder	PPSGF40, DN 50: Brass and stainless steel
11	Valve body	Brass acc. to DIN EN 50930 - 6 or stainless steel 1.4408 (CF8M)

1.) With NBR/EPDM seal
2.) With FKM seal


Visit product website ►

Type 6281



5. Dimensions
5.1. Standard version

- Note:**
- Dimensions in mm
 - The dimensions F1 and G1 apply to G-thread.
 - The dimensions F2 and G2 apply to NPT-thread.
 - The dimensions F3 and G3 apply to Rc-thread.



Coil size	H	J	K	M	O
5	32	20.5	45	41	3.4
6	40	23.5	51	41.4	3.8

DN	A	B	C	D	E	G		NPT		Rc		L	SW	N		
						F1	G1	F2	G2	F3	G3					
10 ¹⁾	83.1	94.1	32	44	22	12	G ¼	10	NPT ¼	–	–	50	22	–		
						12	G ⅝	10.3	NPT ⅝	10.1	Rc ⅝					
10 ²⁾	85.1	98.6			24.5	14	G ½	13.7	NPT ½	–	–	50	27	–		
						22	12	G ¼	10	NPT ¼	–				–	50
	83.6	94.6			12		G ⅝	10.3	NPT ⅝	10.1	Rc ⅝	50	22	–		
						85.6	99.1	24.5	14	G ½	13.7				NPT ½	–
13 ¹⁾	91.1	104.6	42	54.5	27.25				12	G ⅝	–	–	–	–	58	27
						13	32.5	14	G ½	13.7	NPT ½	13.2	Rc ½	65		
93.1	109.1	16			G ¾			14	NPT ¾	–	–	65	32		–	
					20	99.6	115.6	60	74	37	16			G ¾		14
102.1	122.6	37.5									18	G 1	16.8	NPT 1	–	–
					25	106.6	127.1	70	85	46	18	G 1	16.8	NPT 1	16.8	Rc 1
111.6	136.6	20	G 1¼	17.3												

DTS 1000152082 EN Version: R Status: RL (released | freigegeben | valide) printed: 18.12.2024

Visit product website ►

Type 6281



DN	A	B	C	D	E	G		NPT		Rc		L	SW	N
						F1	G1	F2	G2	F3	G3			
40 ¹⁾	120.1	145.1	99	114	61	20	G 1¼	17.3	NPT 1¼	19.1	Rc 1¼	126	50	23
40	125.6	155.6				22	G 1½		NPT 1½		Rc 1½	126	60	
	131.6	166.6			64	24	G 2	17.6	NPT 2	23.4	Rc 2	132	70	
50 ¹⁾	119.9	154.9	115	132	82	24	G 2	17.6	NPT 2	23.4	Rc 2	164	70	37
	119.6	162.1			89.5	27	G 2½	23.6	NPT 2½	–	–	179	85	

1.) Only threaded brass connection
 2.) Only threaded stainless steel connection

DTS 1000152082 EN Version: R Status: RL (released | freigegeben | valide) printed: 18.12.2024


Visit product website ►

Type 6281



5.2. ATEX/IECEx cable version

- Note:**
- Dimensions in mm
 - The dimensions F1 and G1 apply to G-thread.
 - The dimensions F2 and G2 apply to NPT-thread.
 - The dimensions F3 and G3 apply to Rc-thread.
 - For DN 50 see dimensions "5.3. ATEX/IECEx terminal box version" on page 10



Coil size	H	J	K	P	R	S
5	32	20.5	46	68.8	99.8	174.7
6	40	23.5	52	74.8	103	177.7

Visit product website ►

9 | 21

Type 6281




DN	A	B	C	D	E	G		NPT		Rc		L	SW	N	
						F1	G1	F2	G2	F3	G3				
10 ^{1.)}	83.1	94.1	32	44	22	12	G ¼	10	NPT ¼	–	–	50	22	–	
	85.1	98.6				24.5	14	G ½	13.7	NPT ½	–	–	50	27	–
10 ^{2.)}	83.6	94.6				22	12	G ¼	10	NPT ¼	–	–	50	22	–
	85.6	99.1				24.5	14	G ½	13.7	NPT ½	–	–	55	27	–
13 ^{1.)}	91.1	104.6	42	54.5	27.25	12	G ⅝	–	–	–	–	58	27	–	
13						32.5	14	G ½	13.7	NPT ½	13.2	Rc ½	65		27
	93.1	109.1					16	G ¾	14	NPT ¾	–	–	65		32
20	99.6	115.6	60	74	37	16	G ¾	14	NPT ¾	14.5	Rc ¾	80	32	10	
						37.5	18	G 1	16.8	NPT 1	–	–	80		41
25	106.6	127.1	70	85	46	18	G 1	16.8	NPT 1	16.8	Rc 1	95	41	15	
							20	G 1¼	17.3	NPT 1¼	19.1	Rc 1¼	95		50
40 ^{1.)}	120.1	145.1	99	114	61	20	G 1¼	17.3	NPT 1¼	19.1	Rc 1¼	126	50	23	
40	125.6	155.6					22		G 1½			NPT 1½			Rc 1½
						64	24	G 2	17.6	NPT 2	23.4	Rc 2	132		70
50 ^{1.)}	119.9	154.9			115	132	82	24	G 2	17.6	NPT 2	23.4	Rc 2		164
				89.5			27	G 2½	23.6	NPT 2½	–	–	179	85	

1.) Only threaded brass connection
2.) Only threaded stainless steel connection

5.3. ATEX/IECEx terminal box version

- Note:
- Dimensions in mm
 - Standard at DN 50



Coil size	H	J	K	P	R	S
5	32	20.5	46	68.8	99.8	174.7
6	40	23.5	52	74.8	103	177.7

DTS 1000152082 EN Version: R Status: RL (released | freigegeben | valide) printed: 18.12.2024


Visit product website ►

Type 6281



5.4. Compressor relief valves

- Note:**
- Dimensions in mm
 - The dimensions F1 and G1 apply to G-thread.
 - The dimensions F2 and G2 apply to NPT-thread.
 - The dimensions F3 and G3 apply to Rc-thread.



Coil size	H	J	K	M	O
5	32	20.5	46	41	11.2
6	40	23.5	52	41.4	10.8

DN	A	B	C	D	E	G		NPT		Rc		L	SW
						F1	G1	F2	G2	F3	G3		
10	90.5	101.5	32	44	22	12	G ¼	10	NPT ¼	–	–	50	22
	92.5	106			24.5	14	G ½	10.3	NPT ⅜	10.1	Rc ⅜		27
13	90	103.5	42	54.5	27.25	12	G ⅜	–	–	–	–	58	27
	92	108			32.5	16	G ¾	13.7	NPT ½	13.2	Rc ½		32
20	107	123	60	74	37	16	G ¾	14	NPT ¾	14.5	Rc ¾	80	32
	109.5	130			37.5	18	G 1	16.8	NPT 1	–	–		41

DTS 1000152082 EN Version: R Status: RL (released | freigegeben | valide) printed: 18.12.2024

Type 6281

bürkert
FLUID CONTROL SYSTEMS

6. Performance specifications

6.1. Power consumption

Circuit function	Orifice [mm]	Coil size [mm]	AC			DC		ATEX AC/DC Nominal power [W]
			Inrush power [VA]	Holding power [VA]	[W]	Cold [W]	Hot [W]	
A	10...50	32	24	14	8	9.5	8	–
A	10...50	32	24	16	7	9.5	8	–
A / B	13...50	40	–	–	–	–	–	9
A	10	32	–	–	–	–	–	7
B	10	40	–	–	–	–	–	9
B u. CF05	10	32	18	11	5	6	5	–
B u. MX62	13	32	24	14	8	–	–	–
B u. MX62	13	40	–	–	–	11	9.5	–

6.2. Power consumption Kick and Drop coil



Circuit function	Orifice [mm]	Coil size [mm]	Voltage [V]	Inrush power (approx. 500 ms)		Holding power [W]
				[VA]	[W]	
A	10...50	40	024/UC	–	12	0.6
A	10...50	40	230/56	20	–	2
B	10...50	40	024/UC	–	20	2
B	10...50	40	230/56	20	–	2

7. Product accessories

7.1. Cable glands for ATEX/IECEx terminal box

Note:

A polyamide cable gland is included in the scope of delivery. A nickel-plated brass version can be ordered for a surcharge, see [“Cable glands for ATEX/IECEx terminal box” on page 21](#).

Description	Ex approvals		Dimensions										
	Certification	Identification											
Ex cable gland, Nickel-plated brass, 6...13 mm 	PTB 04 ATEX 1112 X, IECEX PTB 13.0027X	II 2 G Ex e IIC Gb, II 2 D Ex tb IIIC Db IP68	 <table><tr><td>TL</td><td>29...37 mm</td></tr><tr><td>L</td><td>6 mm</td></tr><tr><td>D</td><td>20 mm</td></tr><tr><td>SW</td><td>24 mm</td></tr><tr><td>E</td><td>27 mm</td></tr></table>	TL	29...37 mm	L	6 mm	D	20 mm	SW	24 mm	E	27 mm
TL	29...37 mm												
L	6 mm												
D	20 mm												
SW	24 mm												
E	27 mm												
Ex cable gland, Polyamide, 7...13 mm 	PTB 13 ATEX 1015 X, IECEX PTB 13.0034X	II 2 G Ex e IIC Gb, II 2 D Ex tb IIIC Db IP68	 <table><tr><td>TL</td><td>36...45 mm</td></tr><tr><td>L</td><td>10 mm</td></tr><tr><td>D</td><td>20 mm</td></tr><tr><td>SW</td><td>24 mm</td></tr><tr><td>E</td><td>28 mm</td></tr></table>	TL	36...45 mm	L	10 mm	D	20 mm	SW	24 mm	E	28 mm
TL	36...45 mm												
L	10 mm												
D	20 mm												
SW	24 mm												
E	28 mm												

Visit product website ►

12 | 21

Type 6281



7.2. Special tool to turn the terminal box

Note:

This special tool is not included in the scope of delivery of the valve, see "Cable glands for ATEX/IECEx terminal box" on page 21.

Description	Components of the set
Set SC02-AC10 	- Special wrench - Service manual

8. Ordering information

8.1. Bürkert eShop



Bürkert eShop – Easy ordering and quick delivery

You want to find your desired Bürkert product or spare part quickly and order directly? Our online shop is available for you 24/7. Sign up and enjoy all the benefits.

[Order online now](#)

8.2. Bürkert product filter



Bürkert product filter – Get quickly to the right product

You want to select products comfortably based on your technical requirements? Use the Bürkert product filter and find suitable articles for your application quickly and easily.

[Try out our product filter](#)

8.3. Bürkert Product Enquiry Form



Bürkert Product Enquiry Form – Your enquiry quickly and compactly

Would you like to make a specific product enquiry based on your technical requirements? Use our Product Enquiry Form for this purpose. There you will find all the relevant information for your Bürkert contact. This will enable us to provide you with the best possible advice.

[Fill out the form now](#)

Visit product website ►

13 | 21

Type 6281






8.4. Ordering chart

Standard version with brass body

Circuit function A

Note:

Please note that the cable plug must be ordered separately, see "8.5. Ordering chart accessories" on page 20 or separate data sheet for Type 2518 ▶


Circuit function	Port connection	Orifice	K _v value water ^{1) 2)}	Pressure range ³⁾	Weight	Article no.			
		[mm]	[m³/h]	[bar]	[kg]	024/DC [V/Hz]	024/50...60 [V/Hz]	230/50...60 [V/Hz]	
Seal material NBR, polyamide coil, medium temperature - 10 °C...+ 80 °C									
CF A 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.43	322499	322500	322501	
	G ⅜	10	1.9	0.2...16	0.40	322502	322503	322504	
	G ⅜	13	3.8	0.2...16	0.58	221841	221842	221843	
	G ½	13	3.8	0.2...16	0.54	221844	221845	221846	
	G ¾	13	3.8	0.2...16	0.59	221847	221848	221849	
	G ¾	20	8.5	0.2...16	0.89	221850	221851	221852	
	G 1	20	8.5	0.2...16	1.0	221853	221854	221855	
	G 1	25	12	0.2...16	1.3	221856	221857	221858	
	G 1¼	25	12	0.2...16	1.5	221859	221860	221861	
	G 1¼	40	23	0.2...16	2.7	270131	268550	270132	
	G 1½	40	30	0.2...16	3.0	221862	221863	221864	
	G 2	40	30	0.2...16	3.2	221865	221866	221867	
	G 2	50	40	0.2...16	4.5	253156	253157	253158	
	G 2½	50	40	0.2...16	5.2	253159	253160	253161	
Seal material NBR, polyamide coil, medium temperature - 10 °C...+ 80 °C, with manual override									
CF A 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.43	322505	322506	322507	
	G ⅜	10	1.9	0.2...16	0.40	322508	322509	322510	
	G ½	13	3.8	0.2...16	0.54	221952	o. r.	221953	
	G ¾	13	3.8	0.2...16	0.59	221954	o. r.	221955	
	G ¾	20	8.5	0.2...16	0.89	221956	o. r.	221957	
	G 1	20	8.5	0.2...16	1.0	221958	o. r.	221959	
	G 1	25	12	0.2...16	1.3	221960	o. r.	221961	
	G 1¼	25	12	0.2...16	1.5	221962	o. r.	221963	
	G 1¼	40	23	0.2...16	2.7	270142	o. r.	270143	
	G 1½	40	30	0.2...16	3.0	221964	o. r.	221965	
	G 2	40	30	0.2...16	3.2	221966	o. r.	221967	
	Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C								
	CF A 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.43	322511	322512	322513
		G ⅜	10	1.9	0.2...16	0.40	322514	322515	322516
G ⅜		13	3.8	0.2...16	0.58	221868	221869	221870	
G ½		13	3.8	0.2...16	0.54	221871	221872	221873	
G ¾		13	3.8	0.2...16	0.59	221874	221875	221876	
G ¾		20	8.5	0.2...16	0.89	221877	221878	221879	
G 1		20	8.5	0.2...16	1.0	221880	221881	221882	
G 1		25	12	0.2...16	1.3	221883	221884	221885	
G 1¼		25	12	0.2...16	1.5	221886	221887	221888	
G 1¼		40	23	0.2...16	2.7	270133	270134	270135	
G 1½		40	30	0.2...16	3.0	221889	221890	221891	
G 2		40	30	0.2...16	3.2	221892	221893	221894	
G 2		50	40	0.2...16	4.5	253168	253169	253170	
G 2½		50	40	0.2...16	5.2	253171	253172	253173	

DTS 1000152082 EN Version: R Status: RL (released | freigegeben | valide) printed: 18.12.2024

Visit product website ▶

14 | 21

Type 6281

Circuit function	Port connection	Orifice	K _v value water ^{1) 2)}	Pressure range ³⁾	Weight	Article no.		
		[mm]	[m³/h]	[bar]	[kg]	[V/Hz]	[V/Hz]	[V/Hz]
Seal material EPDM, polyamide coil, medium temperature - 30 °C...+ 90 °C								
CFA 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.43	322517 ₺	322518 ₺	322519 ₺
	G ⅜	10	1.9	0.2...16	0.40	322520 ₺	322521 ₺	322522 ₺
	G ⅝	13	3.8	0.2...16	0.58	221895 ₺	221896 ₺	221897 ₺
	G ½	13	3.8	0.2...16	0.54	221898 ₺	221899 ₺	221900 ₺
	G ¾	13	3.8	0.2...16	0.59	221901 ₺	221902 ₺	221903 ₺
	G ¾	20	8.5	0.2...16	0.89	221904 ₺	221905 ₺	221906 ₺
	G 1	20	8.5	0.2...16	1.0	221907 ₺	221908 ₺	221909 ₺
	G 1	25	12	0.2...16	1.3	221910 ₺	221911 ₺	221912 ₺
	G 1¼	25	12	0.2...16	1.5	221913 ₺	221914 ₺	221915 ₺
	G 1¼	40	23	0.2...16	2.7	270136 ₺	270137 ₺	270138 ₺
	G 1½	40	30	0.2...16	3.0	221916 ₺	221917 ₺	221918 ₺
	G 2	40	30	0.2...16	3.2	221919 ₺	221920 ₺	221921 ₺
	G 2	50 ⁴⁾	40	0.2...16	4.5	253162 ₺	253163 ₺	253164 ₺
	G 2½	50 ⁴⁾	40	0.2...16	5.2	253165 ₺	253166 ₺	253167 ₺

o. r. = on request

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.


3.) Pressure data: overpressure to atmospheric pressure

4.) Approved for drinking water according to KTW and W270

Circuit function B

Note:

Please note that the cable plug must be ordered separately, see "8.5. Ordering chart accessories" on page 20 or separate data sheet for Type 2518 ▶.

Circuit function	Port connection	Orifice	K _v value water ^{1) 2)}	Pressure range ³⁾	Weight	Article no.		
		[mm]	[m³/h]	[bar]	[kg]	024/DC [V/Hz]	024/50 [V/Hz]	230/50 [V/Hz]
Seal material NBR, epoxy coil, medium temperature -10 °C...+ 80 °C								
CF B 2/2-way solenoid valve Servo-controlled Normally open 	G ¼	10	1.5	0.2...16	0.43	322523 𐞀	322524 𐞀	322525 𐞀
	G ⅜	10	1.9	0.2...16	0.40	322526 𐞀	322527 𐞀	322528 𐞀
	G ⅝	13	3.8	0.2...16	0.58	221923 𐞀	221924 𐞀	221925 𐞀
	G ½	13	3.8	0.2...16	0.54	221926 𐞀	221928 𐞀	221929 𐞀
	G ¾	13	3.8	0.2...16	0.59	221930 𐞀	221931 𐞀	221933 𐞀
	G ¾	20	8.5	0.2...16	0.89	221934 𐞀	221935 𐞀	221936 𐞀
	G 1	20	8.5	0.2...16	1.0	221937 𐞀	221938 𐞀	221939 𐞀
	G 1	25	12	0.2...16	1.3	221940 𐞀	221941 𐞀	221942 𐞀
	G 1¼	25	12	0.2...16	1.5	221943 𐞀	221944 𐞀	221945 𐞀
	G 1¼	40	23	0.2...16	2.7	270139 𐞀	270140 𐞀	270141 𐞀
	G 1½	40	30	0.2...16	3.0	221946 𐞀	221947 𐞀	221948 𐞀
	G 2	40	30	0.2...16	3.2	221949 𐞀	221950 𐞀	221951 𐞀
	G 2	50	40	0.2...16	4.5	253174 𐞀	253175 𐞀	253176 𐞀
	G 2½	50	40	0.2...16	5.2	253177 𐞀	253178 𐞀	253179 𐞀

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

Visit product website ▶

15 | 21

Type 6281



Circuit function A, with Kick and Drop coil

Note:

- Please note that the cable plug must be ordered separately, see ["8.5. Ordering chart accessories" on page 20](#) or separate data sheet for **Type 2518** ▶.
- The Kick and Drop coil (AC/DC) features integrated electronics for short-term power increase and decrease in double coil technology.

Circuit function	Port connection	Orifice	K _v value water ^{1) 2)}	Pressure range ³⁾	Weight	Article no.	
		[mm]	[m³/h]	[bar]	[kg]	024 / AC/DC [V/Hz]	230 / 50...60 [V/Hz]
	Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C						
CFA 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.43	20046906 	20046961 
	G ⅜	10	1.9	0.2...16	0.40	20046907 	20046960 
	G ½	13	3.8	0.2...16	0.54	20046908 	20046963 
	G ¾	20	8.5	0.2...16	0.89	20046909 	20046964 
	G 1	25	12	0.2...16	1.3	20046910 	20046965 
	G 1¼	40	23	0.2...16	2.7	20046911 	20046966 
	G 1½	40	30	0.2...16	3.0	20046912 	20046967 
	G 2	50	40	0.2...16	4.5	20046913 	20046968 
	G 2½	50	40	0.2...16	5.2	20046914 	20046969 

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet


2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

Circuit function B, with Kick and Drop coil

Note:

- Please note that the cable plug must be ordered separately, see ["8.5. Ordering chart accessories" on page 20](#) or separate data sheet for **Type 2518** ▶.
- The Kick and Drop coil (AC/DC) features integrated electronics for short-term power increase and decrease in double coil technology.

Circuit function	Port connection	Orifice	K _v value water ^{1) 2)}	Pressure range ³⁾	Weight	Article no.	
						024 / AC/DC	230 / 50...60
			[mm]	[m³/h]	[bar]	[kg]	[V/Hz]
Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C							
CF B	G ¼	10	1.5	0.2...16	0.43	20046924 	20046970 
2/2-way solenoid valve	G ⅜	10	1.9	0.2...16	0.40	20046925 	20046971 
Servo-controlled	G ½	13	3.8	0.2...16	0.54	20046927 	20046972 
Normally open	G ¾	20	8.5	0.2...16	0.89	20046928 	20046973 
	G 1	25	12	0.2...16	1.3	20046929 	20046974 
	G 1¼	40	23	0.2...16	2.7	20046930 	20046975 
	G 1½	40	30	0.2...16	3.0	20046931 	20046976 
	G 2	50	40	0.2...16	4.5	20046932 	20046978 
	G 2½	50	40	0.2...16	5.2	20046933 	20046979 

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure





Visit product website ▶

16 | 21

Type 6281

Standard version with stainless steel body
Circuit function A
Note:

Please note that the cable plug must be ordered separately, see ["8.5. Ordering chart accessories"](#) on page 20 or separate data sheet for **Type 2518** ▶

Circuit function	Port connection	Orifice	K _v value water ^{1) 2)}	Pressure range ³⁾	Weight	Article no.		
		[mm]	[m³/h]	[bar]		[kg]	024/DC [V/Hz]	024/50...60 [V/Hz]
Seal material NBR, polyamide coil, medium temperature - 10 °C...+ 80 °C								
CFA 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.43	322529 ☹	322530 ☹	322531 ☹
	G ⅜	10	1.9	0.2...16	0.40	322532 ☹	322533 ☹	322534 ☹
	G ½	13	3.8	0.2...16	0.54	221968 ☹	221969 ☹	221970 ☹
	G ¾	20	8.5	0.2...16	0.86	221971 ☹	221972 ☹	221973 ☹
	G 1	20	8.5	0.2...16	0.97	221974 ☹	221975 ☹	221976 ☹
	G 1	25	12	0.2...16	1.3	221977 ☹	221978 ☹	221979 ☹
	G 1¼	25	12	0.2...16	1.4	221980 ☹	221981 ☹	221982 ☹
	G 1½	40	30	0.2...16	2.8	221983 ☹	221984 ☹	221985 ☹
	G 2	40	30	0.2...16	3.0	221986 ☹	221987 ☹	221988 ☹
Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C								
CFA 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.43	322535 ☹	322536 ☹	322537 ☹
	G ⅜	10	1.9	0.2...16	0.40	322538 ☹	322539 ☹	322540 ☹
	G ½	13	3.8	0.2...16	0.54	221989 ☹	221990 ☹	221991 ☹
	G ¾	20	8.5	0.2...16	0.86	221992 ☹	221993 ☹	221994 ☹
	G 1	20	8.5	0.2...16	0.97	221995 ☹	221996 ☹	221997 ☹
	G 1	25	12	0.2...16	1.3	221998 ☹	221999 ☹	222000 ☹
	G 1¼	25	12	0.2...16	1.4	222001 ☹	222002 ☹	222003 ☹
	G 1½	40	30	0.2...16	2.8	222004 ☹	222005 ☹	222006 ☹
	G 2	40	30	0.2...16	3.0	222007 ☹	222008 ☹	222009 ☹
Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C, with manual override								
CFA 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.43	323894 ☹	o. r.	323968 ☹
	G ⅜	10	1.9	0.2...16	0.40	323971 ☹	o. r.	323972 ☹
	G ½	13	3.8	0.2...16	0.54	323973 ☹	o. r.	323975 ☹
	G ¾	20	8.5	0.2...16	0.86	323977 ☹	o. r.	323978 ☹
	G 1	25	12	0.2...16	1.3	323979 ☹	o. r.	323980 ☹
	G 1¼	25	1.4	0.2...16	1.4	323982 ☹	o. r.	323984 ☹
	G 1½	40	30	0.2...16	2.8	323986 ☹	o. r.	323987 ☹
	G 2	40	30	0.2...16	3.0	323988 ☹	o. r.	323989 ☹
Seal material EPDM, polyamide coil, medium temperature - 30 °C...+ 90 °C								
CFA 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.43	322541 ☹	322542 ☹	322543 ☹
	G ⅜	10	1.9	0.2...16	0.40	322544 ☹	322545 ☹	322546 ☹
	G ½	13	3.8	0.2...16	0.54	222010 ☹	222011 ☹	222012 ☹
	G ¾	20	8.5	0.2...16	0.86	222013 ☹	222014 ☹	222015 ☹
	G 1	20	8.5	0.2...16	0.97	222016 ☹	222017 ☹	222018 ☹
	G 1	25	12	0.2...16	1.3	222019 ☹	222020 ☹	222021 ☹
	G 1¼	25	12	0.2...16	1.4	222022 ☹	222023 ☹	222024 ☹
	G 1½	40	30	0.2...16	2.8	222025 ☹	222026 ☹	222027 ☹
	G 2	40	30	0.2...16	3.0	222028 ☹	222029 ☹	222031 ☹

o. r. = on request

1.) Measurement at +20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

Visit product website ▶

17 | 21


Type 6281



Circuit function B

Note:

Please note that the cable plug must be ordered separately, see "8.5. Ordering chart accessories" on page 20 or separate data sheet for Type 2518 ▶.

Circuit function	Port connection	Orifice	K _v value water ^{1) 2)}	Pressure range ³⁾	Weight	Article no.		
		[mm]	[m³/h]	[bar]	[kg]	024/DC [V/Hz]	024/50 [V/Hz]	230/50 [V/Hz]
Seal material FKM, epoxy coil, medium temperature 0 °C...+ 120 °C								
CF B 2/2-way solenoid valve Servo-controlled Normally open 	G ¼	10	1.5	0.2...16	0.43	322547 	322548 	322549 
	G ⅜	10	1.9	0.2...16	0.40	322550 	322551 	322552 
	G ½	13	3.8	0.2...16	0.54	228387 	228388 	228389 
	G ¾	20	8.5	0.2...16	0.86	228390 	228391 	228392 
	G 1	25	12	0.2...16	1.3	228393 	228394 	228395 
	G 1¼	25	12	0.2...16	1.4	228396 	228397 	228398 
	G 1½	40	30	0.2...16	2.8	228399 	228400 	228401 
	G 2	40	30	0.2...16	3.0	228402 	228403 	228404 

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet



2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

ATEX/IECEx cable version

Note:

- The maximum medium temperature must never exceed the permitted temperature class (T4: + 135 °C, T5: + 100 °C, T6: + 85 °C) minus 5 K.
- Delivery includes 3 metre cable.
- Refer to chapter "3. Approvals and conformities" on page 4 for more information about the approvals.

Circuit function	Port connection	Orifice	K _v value water ^{1) 2)}	Pressure range ³⁾	Weight	Article no.	
		[mm]	[m³/h]	[bar]	[kg]	024 / AC/DC [V/Hz]	230 / AC/DC [V/Hz]
Seal material NBR, brass body, medium temperature - 10 °C...+ 80 °C							
CF A 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.62	349656 𐞀	349658 𐞀
	G ⅜	10	1.9	0.2...16	0.59	349660 𐞀	349662 𐞀
	G ½	13	3.8	0.2...16	0.84	349690 𐞀	349696 𐞀
	G ¾	20	8.5	0.2...16	1.2	349717 𐞀	349719 𐞀
	G 1	25	12	0.2...16	1.7	349731 𐞀	349734 𐞀
	G 1¼	25	12	0.2...16	1.8	349737 𐞀	349739 𐞀
	G 1¼	40	23	0.2...16	3.0	349751 𐞀	349754 𐞀
	G 1½	40	30	0.2...16	3.3	349756 𐞀	349758 𐞀
	G 2	40	30	0.2...16	3.5	349760 𐞀	349762 𐞀
	G 2	50	40	0.2...16	4.8	349773 𐞀	349775 𐞀
G 2½	50	40	0.2...16	5.5	349777 𐞀	349778 𐞀	
Seal material FKM, stainless steel body, medium temperature 0 °C...+ 90 °C							
CF A 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.62	349665 𐞀	349666 𐞀
	G ⅜	10	1.9	0.2...16	0.59	349669 𐞀	349670 𐞀
	G ½	13	3.8	0.2...16	0.84	349707 𐞀	349708 𐞀
	G ¾	20	8.5	0.2...16	1.2	349724 𐞀	349727 𐞀
	G 1	25	12	0.2...16	1.6	349742 𐞀	349744 𐞀
	G 1¼	25	12	0.2...16	1.7	349747 𐞀	349750 𐞀
	G 1½	40	30	0.2...16	3.1	349765 𐞀	349767 𐞀
	G 2	40	30	0.2...16	3.3	349770 𐞀	349771 𐞀

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure

Visit product website ▶



18 | 21

Type 6281



ATEX/IECEx terminal box version

- Note:**
- The maximum medium temperature must never exceed the permitted temperature class (T4: + 135 °C, T5: + 100 °C, T6: + 85 °C) minus 5 K.
 - Refer to chapter "3. Approvals and conformities" on page 4 for more information about the approvals.

Circuit function	Port connection	Orifice	K _v value	Pressure	Weight	Article no.	
		[mm]	water ^{1) 2)}	range ³⁾		024 / AC/DC	230 / AC/DC
			[m³/h]	[bar]	[kg]	[V/Hz]	[V/Hz]
Seal material NBR, brass body, medium temperature - 10 °C...+ 80 °C							
CF A 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.62	349657 ㉞	349659 ㉞
	G ⅜	10	1.9	0.2...16	0.59	349661 ㉞	349663 ㉞
	G ½	13	3.8	0.2...16	0.84	349691 ㉞	349697 ㉞
	G ¾	20	8.5	0.2...16	1.2	349718 ㉞	349720 ㉞
	G 1	25	12	0.2...16	1.7	349733 ㉞	349735 ㉞
	G 1¼	25	12	0.2...16	1.8	349738 ㉞	349740 ㉞
	G 1¼	40	23	0.2...16	3.0	349753 ㉞	349755 ㉞
	G 1½	40	30	0.2...16	3.3	349757 ㉞	349759 ㉞
	G 2	40	30	0.2...16	3.5	349761 ㉞	349763 ㉞
	G 2	50	40	0.2...16	4.8	349774 ㉞	349776 ㉞
Seal material FKM, stainless steel body, medium temperature 0 °C...+ 90 °C							
CF A 2/2-way solenoid valve Servo-controlled Normally closed 	G ¼	10	1.5	0.2...16	0.62	349664 ㉞	349667 ㉞
	G ⅜	10	1.9	0.2...16	0.59	349668 ㉞	349671 ㉞
	G ½	13	3.8	0.2...16	0.84	349705 ㉞	349709 ㉞
	G ¾	20	8.5	0.2...16	1.2	349725 ㉞	349728 ㉞
	G 1	25	12	0.2...16	1.6	349743 ㉞	349745 ㉞
	G 1¼	25	12	0.2...16	1.7	349748 ㉞	349749 ㉞
	G 1½	40	30	0.2...16	3.1	349766 ㉞	349768 ㉞
	G 2	40	30	0.2...16	3.3	349769 ㉞	349772 ㉞

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet
2.) A pressure difference of 0.5 bar is required to open the full cross-section.
3.) Pressure data: overpressure to atmospheric pressure

DTS 1000152082 EN Version: R Status: RL (released | freigegeben | valide) printed: 18.12.2024



Type 6281



Compressor relief valve with brass body

Note:

- Please note that the cable plug must be ordered separately, see ["8.5. Ordering chart accessories" on page 20](#) or separate data sheet for **Type 2518** ▶.
- The valve is open in the rest position. The medium also flows via the exhaust port on the solenoid.

Circuit function	Port connection	Orifice	K _v value water ^{1) 2)}	Pressure range ³⁾	Weight	Article no.			
		[mm]	[m³/h]	[bar]	[kg]	024/DC	024/50...60	110/50...60	230/50...60
Seal material FKM, polyamide coil, medium temperature 0 °C...+ 90 °C, DN 10									
CF B	G ¾	10	1.9	0.2...16	0.43	330985 ☹	330986 ☹	330987 ☹	330988 ☹
2/2-way solenoid valve Servo-controlled Normally open	G ½	10	1.9	0.2...16	0.40	330989 ☹	331007 ☹	331008 ☹	331009 ☹
									
Seal material FKM, polyamide coil, medium temperature 0 °C...+ 90 °C, DN 13									
CF B	G ¾	13	3.6	0.5...16	0.58	310663 ☹	310662 ☹	310661 ☹	310659 ☹
2/2-way solenoid valve Servo-controlled Normally open	G ½	13	3.6	0.5...16	0.54	310667 ☹	310666 ☹	310665 ☹	310664 ☹
									

1.) Measurement at + 20 °C, 1 bar at the valve inlet and free outlet

2.) A pressure difference of 0.5 bar is required to open the full cross-section.

3.) Pressure data: overpressure to atmospheric pressure


Further versions on request	
 Material Brass dezincification resistant	 Temperature • EPDM version up to + 100 °C with epoxy coil • FKM version up to + 120 °C with epoxy coil
 Process connection NPT, Rc	 Approval Further information can be found in chapter "3. Approvals and conformities" on page 4 .
 Voltage Further voltages	

8.5. Ordering chart accessories

Cable plug Type 2518, form A according to DIN EN 175301 - 803

Note:

For further versions see data sheet **Type 2518** ▶.

Cable plug	Dimensions	Version	Voltage	Article no.
		Without circuitry (AC/DC)	0...250 V AC/DC	314802 ☹
		With LED (AC/DC)	12...24 V AC/DC	314812 ☹
		With LED and varistor (AC/DC)	12...24 V AC/DC	314820 ☹
		With rectifier, LED and varistor	12...24 V AC/DC	314816 ☹
		Without circuitry (AC/DC) with silicone seal for higher ambient temperature, e.g. steam version (NA07)	0...250 V AC/DC	361687 ☹

Visit product website ▶


20 | 21

Type 6281



Cable plug Type 2509, form A according to DIN EN 175301 - 803

- Note:**
- Without circuitry (standard)
 - Refer to data sheet **Type 2509** ▶ for more information about the cable plug.

Cable plug	Dimensions	Version	Voltage	Article no.
		Without circuitry	0...250 V AC/DC	137943 



Cable glands for ATEX/IECEx terminal box

- Note:**
- A cable gland in polyamide version is included in the delivery. A nickel-plated brass version can be ordered at surcharge.
 - Refer to **"7.1. Cable glands for ATEX/IECEx terminal box"** on page 12 for more information about Ex cable glands.
 - Refer to **"7.2. Special tool to turn the terminal box"** on page 13 for more information about Special wrench.

Description	Article no.
Ex cable gland, nickel-plated brass, 6...13 mm ¹⁾	773278 
Ex cable gland, polyamide, 7...13 mm ¹⁾	773277 
Set SC02-AC10: special wrench ²⁾ incl. service manual	293488 

1.) Cable diameter
2.) Not included in the scope of delivery of the valve

Mounting set for DN 10

Cable plug	Dimensions	Description	Article no.
		Mounting bracket kit (consisting of mounting bracket and screws)	365730 

DTS 1000152082 EN Version: R Status: RL (released | freigegeben | valide) printed: 18.12.2024

Visit product website ▶