Safety coupling I.D. 7.6

»R320ST« series

MAX

Art. No. **187874**

Type No. **416.08-SL.B**







Exemplary illustration

Technical data

Sealant	NBR
Flow rate measurement	at 6 bar and Δ_p = 0.5 bar
Max. operating pressure	16 bar
Min. medium temperature	-20 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Max. ambient temperature	100 °C
Material	Steel / zinc-plated lead-free brass
Spring	Lead-free stainless steel
Flow rate (air)	2250 l/min
a/f 1	19 mm
a/f 2	20 mm
DN	7.6
Length	68.1 mm
for hose I.D.	8 mm
for tube O.D.	12 mm

Commercial data

Customs tariff number	84812090
Country of origin	SE
eCl@ss 5.1.4	27294205
eCl@ss 9.0	27294205
UNSPSC_Code_v190501	27131613
UNSPSC_CodeDesc_v190501	Air coupling

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
16.11.2026 The specified data do not represent legally guaranteed properties.

Material informations

RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
16.11.2026 The specified data do not represent legally guaranteed properties.