


Stainless steel ball valve

Stainless steel, 2-piece - standard type, lockable

STAINLESS STEEL

Art. No. 135900

Type No. 3395.09



Exemplary illustration

Technical data

Housing	Stainless steel 1.4408
Ball	Stainless steel 1.4401
Ball seal	PTFE (15 % glass fibre reinforced)
Stem seal	PTFE
Hand lever	stainless steel 1.4301, with plastic coating
Operating temperature	-20 to 180 °C
PN	40 bar
Standard thread	G-thread DIN EN ISO 228-1, R-thread DIN EN 10226 (ISO 7-1)
Thread	G 2 1/2
C Ø	64.0 mm
DN	65
L	138.0 mm
A	240.0 mm
B	135.0 mm
E	21.0 mm
F	21.0 mm
Flow rate kv value	265 m³/h
Bore diameter padlock	ca. 6.0 mm

Stainless steel ball valve, IT/IT thread, with full bore

Commercial data

Customs tariff number	84818081
Country of origin	CN
eCl@ss 5.1.4	27292002
eCl@ss 9.0	27292002
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

Material informations

RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

Pressure-temperature rating

PN40

