
Ball valve

MAX

Art. No. 147606

Type No. 3350.66-1





Exemplary illustration

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Technical data

Operating temperature	-20 to 130 °C
PN	80 bar
DN	25 mm
Thread	G 1
Standard thread	DIN EN ISO 228-1
Thread material	bright brass
Housing	nickel-plated brass
Ball	chrome-plated brass
Ball seal	PTFE
Stem seal	PTFE
Hand lever	aluminium, painted black
a/f 1	39 mm
a/f 2	39 mm
A	120 mm
B	79 mm
E	13,5 mm
F	13,5 mm
L	87 mm

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
09.12.2025 The specified data do not represent legally guaranteed properties.

Commercial data

Country of origin	IT
Customs tariff number	84818081
eCl@ss 5.1.4	27292002
eCl@ss 9.0	27292002
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
09.12.2025 The specified data do not represent legally guaranteed properties.