

RIEGLER
Druckluft und Pneumatik

Bohr- und Schneidöl-Spray





Cutting fluid

Cutting fluid is free from mineral oil. Its exceptionally high lubricating performance allows increased cutting speeds, extended tool life and, consequently, enhanced cutting efficiency of the tools.

Applications:
- drilling and turning
- milling and grinding
- sawing and punching
- thread cutting of all types of steel, castings, stainless steel, copper, brass, aluminium, and their alloys

Directions:
Shake can thoroughly before use. Richly spray on at 20 to 25 cm from surface.

Extremely flammable aerosol. Pressurized container: may burst if heated. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



Gefahr
Danger

4 047322 073103

Bohr- und Schneidöl-Spray ist mineralölfrei. Es ermöglicht durch seine besonders hohe Schmierwirkung größere Schnittgeschwindigkeiten, höhere Standzeiten und dadurch auch eine höhere Schneidleistung der Werkzeuge.

Anwendungsgebiete:
- Bohren und Drehen
- Fräsen und Reiben
- Sägen und Stanzen
- zum Gewindeschneiden aller Stahlsorten, Guss, Edelstähle, Kupfer, Messing, Aluminium und anderen Legierungen

Gebrauchsanweisung:
Dose vor Gebrauch gründlich schütteln. Aus ca. 20–25 cm Entfernung satt aufsprühen.

Extrem entzündbares Aerosol. Behälter steht unter Druck: Kann bei Erwärmung bersten. Ist ärztlicher Rat erforderlich, Verpackung oder Kennzeichnungsetikett bereithalten. Darf nicht in die Hände von Kindern gelangen. Von Hitze, heißen Oberflächen, Funken, offenen Flammen sowie anderen Zündquellenarten fernhalten. Nicht rauchen. Nicht gegen offene Flamme oder andere Zündquelle sprühen. Nicht durchstechen oder verbrennen, auch nicht nach Gebrauch. Vor Sonnenbestrahlung schützen. Nicht Temperaturen über 50 °C/122 °F aussetzen.

RIEGLER & Co. KG
Schützenstraße 27 • 72574 Bad Urach
07125 9497-0 • vertrieb@riegler.de • www.riegler.de

400 ml 520 UFI: CJS2-C0H8-000S-MACU

Best.-Nr. 192330