
Push-in T-fitting

»metallica« series

PLUS

Art. No. 137013

Type No. 855.012-14



Exemplary illustration

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion

Technical data

Max. working pressure	16 bar
Operating temperature	-20 to 150 °C
Series	metallica
Material	nickel-plated brass
Medium	compressed air
Sealant	FKM, FPM
Sleeve	nickel-plated brass
Clamping ring	stainless steel
Applications	compressed air systems, welding technology, vacuum
Recommended hose/tube material	PA, PU
Thread form	parallel male thread
Version	with O-ring
Design	swivel type
Thread	G 1/2 ET
for tube O.D.	14 mm
L1	64.0 mm
L2	33.5 mm
a/f	20 mm


RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
02.10.2026 The specified data do not represent legally guaranteed properties.

Commercial data

Customs tariff number	74122000
Country of origin	IT
eCl@ss 5.1.4	27294201
eCl@ss 9.0	27294201
UNSPSC_Code_v190501	27131613
UNSPSC_CodeDesc_v190501	Air coupling

Dimensions



Thread	for tube O.D.	Ø B	H	a/f	L1	L2
	mm	mm	mm	mm	mm	mm
G 1/2 ET	14	25.0	11.0	20	64.0	33.5

Accessories

	Art. No.	Type No.
Loosening tool for quick-connect fittings, for hose exterior Ø 4 - 14 mm	121863	LW4-14
Plug nipple »metallica«,hose exterior Ø14, Working pressure -0.98 to 16 bar, Operating temp. -20 °C to 80 °C, nickel-plated brass	129491	8865.014
Locking plug »value line«, plug conn. 14 mm, working pressure -0.98 to 16 bar, temperature -20 °C to 80 °C, nickel-plated brass	129490	58.014-E

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
02.10.2026 The specified data do not represent legally guaranteed properties.