


# Stainless steel ball valve

Stainless steel, 2-piece - length acc. to DIN 3202-M3, lockable

## STAINLESS STEEL

Art. No. 135356

Type No. 397.06



Exemplary illustration

## Technical data

|                       |                                              |
|-----------------------|----------------------------------------------|
| Housing               | Stainless steel 1.4408                       |
| Ball                  | Stainless steel 1.4401                       |
| Ball seal             | PTFE (15 % glass fibre reinforced)           |
| Stem seal             | PTFE                                         |
| Hand lever            | stainless steel 1.4301, with plastic coating |
| Operating pressure    | max. 63 bar (dependent on temperature)       |
| Operating temperature | -20 to 180 °C                                |
| PN                    | 63 bar                                       |
| Standard thread       | DIN EN ISO 228-1                             |
| Thread                | G 1 1/4                                      |
| C Ø                   | 32.0 mm                                      |
| DN                    | 32                                           |
| L                     | 110.0 mm                                     |
| A                     | 150.0 mm                                     |
| B                     | 82.0 mm                                      |
| E                     | 22.0 mm                                      |
| F                     | 22.0 mm                                      |
| Flow rate kv value    | 57 m³/h                                      |
| Bore diameter padlock | ca. 7.5 mm                                   |

Stainless steel ball valve with full passage

## Commercial data

|                         |                  |
|-------------------------|------------------|
| Customs tariff number   | 84818081         |
| Country of origin       | CN               |
| eCl@ss 5.1.4            | 27292002         |
| eCl@ss 9.0              | 27292002         |
| UNSPSC_Code_v190501     | 40141603         |
| UNSPSC_CodeDesc_v190501 | Pneumatic valves |

## Material informations

|                       |                            |
|-----------------------|----------------------------|
| RoHS materials notice | RoHS compliant             |
| REACH Info            | no SVHC substance included |

## Pressure-temperature rating

