T-piece

zinc plated - DIN DVGW

Art. No. **112969**

Type No. **TFT 130-3814**

Exemplary illustration

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for pipe construction.
These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.
They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust.
These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines.

Working minimal temperature = -20 °C, 25 bar.
Working pressure for temperature range from -20 °C to 120 °C: 25 bar.
Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Technical data

Material	black malleable iron B350-10, design symbol A
Temperature range	-20 to 300 °C
Surface	hot dip galvanised
Standard thread	acc. ISO 7-1
Version	reducing
Thread 1	Rp 3/8 IT
Thread 2	Rp 1/4 IT
Thread 3	Rp 3/8 IT

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
The specified data do not represent legally guaranteed properties.

Commercial data

Customs tariff number	73071910
Country of origin	CN
eCl@ss 5.1.4	37200106
eCl@ss 9.0	22560202
UNSPSC_Code_v190501	40174603
UNSPSC_CodeDesc_v190501	Cast iron pipe tee

Dimensions



Thread 1	Thread 2	Thread 3	A	B	Z1	Z2
			mm	mm	mm	mm
Rp 3/8 IT	Rp 1/4 IT	Rp 3/8 IT	23.0	23.0	13.0	13.0

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
05.05.2025 The specified data do not represent legally guaranteed properties.