Throttle valve

in block design

MAX

Art. No. 103812

Type No. 225.56



Exemplary illustration

Straight-way valves with restricted flow in both directions.

Technical data

Function	both directions throttling
Version	adjustable with knurled screw
Design	block type
Connection	G 1/2 IT
Thread for panel mounting	M22x1.5
Medium	filtered, lubricated compressed air
Operating pressure	max. 10 bar
Operating temperature	-10 to 70 °C
Housing	anodised aluminium
Sealant	NBR
Internal parts	nickel-plated brass
a/f	26 mm
A	65.0 mm
C	30.0 mm
E	50.0 mm
I	29.0 mm
L	6.5 mm
M	33.0 mm

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
22.10.2026 The specified data do not represent legally guaranteed properties.

Commercial data

Customs tariff number	74122000
Country of origin	IT
eCl@ss 5.1.4	27292202
eCl@ss 9.0	27292202
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

Flow chart



Materials

Part	Materials
Body	Anodised Al
Nipple	CW 614 N
Control head	CW 614 N
Throttle valve	CW 614 N
Stem	CW 614 N
Fixing nut	CW 614 N
O-ring	NBR
Locking ring	CW 614 N

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
22.10.2026 The specified data do not represent legally guaranteed properties.

Dimensions [mm]



Connection	L	D3	L1	L2	A	E	L5	C	a/f
	mm	mm	mm	mm	mm	mm	mm	mm	mm
G 1/2 IT	6.5	22x1.5	40.0	92.0	65.0	50.0	17.0	30.0	26

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
22.10.2026 The specified data do not represent legally guaranteed properties.