3/2-way valve

mechanically operated - »M3« series

EASY

Art. No. **115956**

Type No. **511.2000**



Exemplary illustration

3/2-way valves

- Mechanically operated -

Technical data

Operation	mechanical
Function	3/2 NC
Version	roller lever
Connection	G 1/8 IT
Exhaust connection	G 1/8 IT
Flow cross-section	9.0 mm² (Cv = 0.50)
Flow rate measurement	at P_1 = 8 bar, P_2 = 6 bar and pressure drop Δ_p = 1 bar
Flow rate	450 l/min
Medium	filtered compressed air (min. ≤ 40 µm) with or without lubrication. If lubricated, then continuous.
Operating pressure	0 - 10 bar
Test pressure	15 bar
Temperature range	-20 to 70 °C
Valve body	aluminium alloy
Series	M3

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
28.10.2026 The specified data do not represent legally guaranteed properties.

Commercial data

Customs tariff number	84818079
Country of origin	CN
eCl@ss 5.1.4	27291701
eCl@ss 9.0	27291390
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

Flow chart



RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
28.10.2026 The specified data do not represent legally guaranteed properties.

Components and material



No.	Item	Material
1	Cover	PA66
2	Screw	Steel
3	Spring	Stainless steel
4	Spacer	POM
5	Body	Aluminium alloy
6	Screw	Steel
7	Holder	Steel
8	Roller	Hardened steel
9	Roller lever	Steel
10	Press bolt	Steel
11	Screw	Steel
12	Cover	Aluminium alloy
13	O-ring	NBR
14	Spool	Aluminium alloy
15	Centering bush	Aluminium alloy

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
28.10.2026 The specified data do not represent legally guaranteed properties.

Dimensions [mm]



Connection	Exhaust connection	B	C	D	E	F	G	H	J	K	L
		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
G 1/8 IT	G 1/8 IT	22.0	28.5	58.0	63.8	28.5	23.5	35.0	18.5	20.0	4.3

M	N
mm	mm
18.5	20.0

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
28.10.2026 The specified data do not represent legally guaranteed properties.

Technical information

Port identification pneumatic valves

	Designation at the valve	corresponds to ISO 1219-1
Input port	P	1
Output port	A	2
Output port	B	4
Exhaust port	R	3
Exhaust port	S	5
Control port	Y	12
Control port	Z	14

Reversal stroke

Version	Spool stroke	Button/lever stroke
Plunger	2.0 to 3.3	-
Roller lever	2.0 to 3.0	4.6 to 6.8
Roller lever with free return	2.0 to 3.0	5.0 to 7.8

Assembly chart

Body mounting

Fixed plate



Panel mounting

Fixed plate



RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
28.10.2026 The specified data do not represent legally guaranteed properties.