


Stainless steel ball valve

Stainless steel, 2-piece - length acc. to DIN 3202-M3, lockable

STAINLESS STEEL

Art. No. 135352

Type No. 397.02



Exemplary illustration

Technical data

Housing	Stainless steel 1.4408
Ball	Stainless steel 1.4401
Ball seal	PTFE (15 % glass fibre reinforced)
Stem seal	PTFE
Hand lever	stainless steel 1.4301, with plastic coating
Operating pressure	max. 63 bar (dependent on temperature)
Operating temperature	-20 to 180 °C
PN	63 bar
Standard thread	DIN EN ISO 228-1
Thread	G 3/8
C Ø	12.0 mm
DN	10
L	60.0 mm
A	98.0 mm
B	58.0 mm
E	12.0 mm
F	12.0 mm
Flow rate kv value	7.9 m ³ /h
Bore diameter padlock	ca. 7.5 mm

Stainless steel ball valve with full passage

Commercial data

Customs tariff number	84818081
Country of origin	CN
eCl@ss 5.1.4	27292002
eCl@ss 9.0	27292002
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

Material informations

RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

Pressure-temperature rating

