

## GEKA blind coupling

GEKA-plus series, lead-free brass, with KTW approval



Art. No. 154166

Type No. K 118-KTW.MSB



Exemplary illustration

GEKA couplings for potable water, lead-free brass, with KTW approval.  
Lead-free brass (Pb < 0.1%)

### Technical data

|                                      |                                               |
|--------------------------------------|-----------------------------------------------|
| Max. operating pressure              | 40 bar                                        |
| Medium temperature                   | -10 to 90 °C                                  |
| Ambient temperature                  | -10 to 90 °C                                  |
| Sealant                              | EPDM for potable water                        |
| KTW approval                         | after D2 and long-term test results DVGW W270 |
| Description                          | blind coupling                                |
| Lead-free brass (lead content <0.1%) | yes                                           |


### Commercial data

|                         |              |
|-------------------------|--------------|
| Customs tariff number   | 74122000     |
| Country of origin       | CN           |
| eCl@ss 5.1.4            | 37110390     |
| eCl@ss 9.0              | 37110390     |
| UNSPSC_Code_v190501     | 40141734     |
| UNSPSC_CodeDesc_v190501 | Hose fitting |

### Material informations

|                       |                            |
|-----------------------|----------------------------|
| RoHS materials notice | RoHS compliant             |
| REACH Info            | no SVHC substance included |

## Dimensions



## Spareparts

|                                                                                                                                   | Art. No. | Type No.  |
|-----------------------------------------------------------------------------------------------------------------------------------|----------|-----------|
| Sealing ring, EPDM blue, for couplings of series GEKA-plus, lead-free brass, with KTW approval, temperature range -10 °C to 90 °C | 154170   | D 300.MSB |