

Reducing nipple

Stainless steel 1.4408

STAINLESS STEEL

Art. No. 119055

Type No. REDNG3412ES4408



Exemplary illustration

Technical data

Working pressure	max. 20 bar
Thread 1	G 1/2 IT
Thread 2	G 3/4 ET
L1	21.0 mm
a/f	27 mm
Thread form	parallel male thread and female thread
Standard thread	DIN EN ISO 228-1
Version	Hexagonal

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).


Commercial data

Customs tariff number	73072910
Country of origin	CN
eCl@ss 5.1.4	22360606
eCl@ss 9.0	22560206
UNSPSC_Code_v190501	40173303
UNSPSC_CodeDesc_v190501	Stainless steel pipe nipple

Material informations

RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

Dimensions



L1	a/f
mm	mm
21.0	27

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).