# Hexagonal counter nut

Stainless steel 1.4408

STAINLESS STEEL

**Art. No.** **119331**

**Type No.** **SKMG18ES4408**



Exemplary illustration

## Technical data

| | |
|---|---|
| Working pressure | max. 20 bar |
| Material | stainless steel 1.4408 |
| Thread | G 1/8 IT |
| a/f | 18 mm |
| Thread form | parallel female thread |
| Standard thread | DIN EN ISO 228-1 |

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a propper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).

## Commercial data

| | |
|---|---|
| Customs tariff number | 73072910 |
| Country of origin | CN |
| eCl@ss 5.1.4 | 27299290 |
| eCl@ss 9.0 | 27299290 |
| UNSPSC_Code_v190501 | 40141616 |
| UNSPSC_CodeDesc_v190501 | Valve parts or accessories |

## Material informations

| | |
|---|---|
| RoHS materials notice | RoHS compliant |
| REACH Info | no SVHC substance included |

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de



Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
05.10.2026 The specified data do not represent legally guaranteed properties.

## Dimensions




| Thread | a/f | A |
|---|---|---|
| | mm | mm |
| G 1/8 IT | 18 | 7.1 |

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a propper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de



Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
05.10.2026 The specified data do not represent legally guaranteed properties.