

Push-in L-fitting

»metallica« series

PLUS ||

Art. No. 130095

Type No. 854.003-3



Exemplary illustration

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Technical data

Max. working pressure	16 bar
Operating temperature	-20 to 150 °C
Series	metallica
Material	nickel-plated brass
Medium	compressed air
Sealant	FKM, FPM
Sleeve	nickel-plated brass
Clamping ring	stainless steel
Applications	compressed air systems, welding technology, vacuum
Recommended hose/tube material	PA, PU
Thread form	parallel male thread
Version	with O-ring
Design	swivel type
Thread	M3 ET
for tube O.D.	3 mm
L1	11.0 mm
L2	12.7 mm
a/f	6 mm


Commercial data

Customs tariff number	74122000
Country of origin	IT
eCl@ss 5.1.4	27294201
eCl@ss 9.0	27294201
UNSPSC_Code_v190501	27131613
UNSPSC_CodeDesc_v190501	Air coupling

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

Dimensions



Thread	for tube O.D.	Ø B	H	a/f	L1	L2
	mm	mm	mm	mm	mm	mm
M3 ET	3	5.8	3.0	6	11.0	12.7