Hexagonal counter nut

Stainless steel 1.4408

STAINLESS STEEL

Art. No. **119336**

Type No. **SKMG34ES4408**



Exemplary illustration

Technical data

Working pressure	max. 20 bar
Material	stainless steel 1.4408
Thread	G 3/4 IT
a/f	36 mm
Thread form	parallel female thread
Standard thread	DIN EN ISO 228-1

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a propper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).

Commercial data

Customs tariff number	73072910
Country of origin	CN
eCl@ss 5.1.4	27299290
eCl@ss 9.0	27299290
UNSPSC_Code_v190501	40141616
UNSPSC_CodeDesc_v190501	Valve parts or accessories


Material informations

RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
21.11.2026 The specified data do not represent legally guaranteed properties.

Dimensions



Thread	a/f	A
	mm	mm
G 3/4 IT	36	9.0

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a propper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
21.11.2026 The specified data do not represent legally guaranteed properties.