


2/2-way solenoid valve

stainless steel - 2/2-way type

STAINLESS STEEL

Art. No. 102976

Type No. MV 121 ES-G



Exemplary illustration

Technical data

Thread	G 1/4
Operating pressure	0 - 3.5 bar
Voltage	24 V DC
Housing	stainless steel 1.4301
Valve seat	stainless steel 1.4301
Internal parts	stainless steel
Sealant	FPM
Medium temperature	-15 to 120 °C
Ambient temperature	-15 to 55 °C
Type	2
Protection IP	IP 65 (with connector socket fitted)
Electrical connection	for connector socket PG 11 P acc. to DIN 4400
Function	normally closed (NC)
DN	4 mm
A	95.0 mm
B	40.0 mm

Commercial data

Customs tariff number	84818073
Country of origin	NL
eCl@ss 5.1.4	27220601
eCl@ss 9.0	27220601
UNSPSC_Code_v190501	40141605
UNSPSC_CodeDesc_v190501	Solenoid valves

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

ASCO™ Solenoid Valves

For High Pressure Fluids | Direct Operated, 1/8" or 1/4" tapped | 15 mm Compression Fittings

Series
262

Features and Benefits

- High operating pressure
- RoHS compliance
- AC/DC interchangeability of the coil possible only for NC (10.1 W/1.6 W and 17.1 W/22.6 W)
- Valves do not require a minimum operating pressure
- Large selection of seal materials providing wide chemical compatibility
- Compliance with UL and CSA standards
- The solenoid valves satisfy all relevant EU directives

General

Differential pressure

See «SPECIFICATIONS» [1 bar = 100 kPa]

Maximum viscosity

65 cSt (mm²/s)

Response time

5 - 25 ms

Fluids (*)	Temperature range (TS)	Seal materials (*)
air, inert gas, water, oil	-25°C to +80°C	NBR (nitrile)
	0°C to +60°C	UR (cast urethane)

Materials in contact with fluid

(*) Ensure that the compatibility of the fluids in contact with the materials is verified

Body Brass or Stainless steel, AISI 304

Shading coil Copper or Silver

Core tube Stainless steel, AISI 305

Core and plugnut Stainless steel, AISI 430F

Springs Stainless steel, AISI 302

Seal NBR

Disc NBR or UR

Disc holder (NO function) PA

Electrical characteristics

Coil insulation class F (AC) or H (DC)

Connector Spade plug (cable Ø 6-10 mm)

Connector specification ISO 4400 / EN 175301-803, form A

Electrical safety IEC 335

Electrical enclosure protection Moulded IP65 (EN 60529)

Standard voltages DC (=) : 24V - 48V

(Other voltages and 60 Hz on request) AC (~) : 24V - 48V - 115V - 230V/50 Hz

Operator ambient temperature range (TS) (°C)	Power ratings				Replacement coil ⁽¹⁾	
	Inrush ~ (VA)	Holding ~ (VA)	Hot/cold = (W)	Hot/cold = (W)	~ 230 V/50 Hz	= 24 V DC
-25 to +55	30	16	8.1	7.7/ 10.6	238213-059	238513-006
	45	20	11.1	12.5/18.6	238213-157	238513-106
	50	25	10.1	8.5/11.6	238613-059	238913-006
	70	40	17.1	15.1/22.6	238613-159	238913-106

⁽¹⁾ All 238 basic numbers are UL & CSA approved and marked with the UR (recognised component) and CSA logos.

Options


- Seals and disc (*) ⁽²⁾
(fluid temperature range)
 - FPM (fluoroelastomer):
-15°C to +100°C (coil class F)
-15°C to +120°C (coil class H)
 - EPDM (ethylene-propylene), 0°C to +100°C
 - CR (chloroprene), 0°C to +80°C
 - PTFE: -15°C to +100°C (coil class F)
-15°C to +120°C (coil class H)

- Oxygen service, FPM disc and seals, see "PRODUCT CODE"
- WRAS approval, EPDM disc and seals, see "PRODUCT CODE"
- Magnetic latching versions, reverse polarity DC voltages, see "PRODUCT CODE FOR MAGNETIC LATCHING VERSION ONLY"
- 15 mm compression-fitting body, supplied with nut and olive, see "PRODUCT CODE"
- Connector with visual indication and peak voltage suppression or with cable length of 2 m
- Explosionproof enclosures for use in zones 1/21-2/22, categories 2-3 to ATEX Directive 2014/34/EU (See page: 4)


⁽²⁾ The minimum ambient temperature of the solenoid valve is determined by the limitations of minimum temperature indicated.



CE



NC function



NO function

ASCO™ Solenoid Valves

For High Pressure Fluids | Direct Operated, 1/8" or 1/4" tapped | 15 mm Compression Fittings

**Series
262**

Specifications

Specifications															PRODUCT CODE										
Pipe size	Orifice size	Flow coefficient			Operating pressure differential (bar)								Power coil (W)		Thread type	Dimensions / type (1)	Brass	Stainless steel	Voltage code						
																			24 V/50 Hz	48 V/50 Hz	115 V/50 Hz	230 V/50 Hz	24 V/DC	48 V/DC	
		Kv																							
		(mm)	(m³/h)	(l/min)	Min.	Max. (PS)						~	=	~											=
~	=	~	=	~	=	~	=	~	=	~	=	~	=	~	=	~	=	~	=						
Without manual operator																									
NC - Normally closed, NBR seal and disc																									
1/8"	1.2	0.05	0.8	0	51	51	51	41	50	34	8.1	10.6	G NPT	01	G262K001S1N00	-									
	2.4	0.18	3	0	25	14	22	10	13	10	8.1	10.6	G NPT	01	G262K014S1N00	-	8262K012S1N00								
	3.2	0.3	5	0	12	8	12	6.5	8	6	8.1	10.6	G NPT	01	G262K002S1N00	-	8262K015S1N00								
					18	10	17	8	13	8	11.1	18.6	G	01	G262K016S1N00	-									
1/4"	1.2	0.05	0.8	0	103	68	103	66	103	58	10.1	11.6	G*	02	E262K200S1W00 (2)	-									
					151	68	151	66	117	58	10.1	11.6	G*	02	-	E262K214S1W00 (2)									
	2.4	0.18	3	0	51	51	51	41	50	34	8.1	10.6	G*	01	E262K019S1N00	-	8262K080S1N00								
					25	14	22	10	11	10	8.1	10.6	G*	01	E262K020S1N00	-									
					34	19	24	13	18	13	11.1	18.6	G*	01	E262K021S1N00	-	8262K086S1N00								
	3.2	0.3	5	0	40	16	28	16	28	15	10.1	11.6	G*	02	E262K108S1N00	E262K182S1N00									
					49	41	28	28	28	27	17.1	22.6	G*	02	E262K109S1N00	E262K183S1N00									
	4	0.45	7.5	0	12	8	12	6.5	6	5.5	8.1	10.6	G*	01	E262K022S1N00	-	8262K007S1N00								
					18	10	17	8	10	7.5	11.1	18.6	G*	01	E262K023S1N00	-									
	5.6	0.63	10.5	0	23	7.5	20	7	14	6.5	10.1	11.6	G*	02	E262K232S1N00	E262K184S1N00									
					34	17	26	17	24	15	17.1	22.6	G*	02	E262K110S1N00	E262K185S1N00									
	7.1	0.76	12.7	0	7	5	7	4	4	4	8.1	10.6	G	01	E262K111S1N00	E262K186S1N00									
					14	3.5	13	3.5	10	3.5	10.1	11.6	G*	02	E262K202S1N00	E262K220S1N00									
	7.1	0.76	12.7	0	20	7.5	14	7.5	14	7.5	17.1	22.6	G*	02	E262K112S1N00	E262K187S1N00									
					6.5	2	6.5	2	6.5	2	10.1	11.6	G*	02	E262K208S1N00	E262K226S1N00									
	7.1	0.76	12.7	0	8.5	4	8.5	4	8.5	4	17.1	22.6	G*	02	E262K114S1N00	E262K188S1N00									
					3.5	2	3.5	2	2.5	1.9	8.1	10.6	G*	01	E262K013S1N00	-									
	7.1	0.76	12.7	0	2	1.6	2	1.5	2	1.3	8.1	10.6	G*	01	E262K090S1N00	-	8262K036S1N00								
					4	1.5	5	1.5	4	1.3	10.1	11.6	G*	02	E262K210S1N00	E262K189S1N00									
	7.1	0.76	12.7	0	6	3	6	3	6	3	17.1	22.6	G*	02	E262K212S1N00	E262K230S1N00									

(1) For dimensions, see drawing(s) for each construction type on the following page(s).

(*) Ensure that compatibility of materials in contact with fluids is verified.

(2) UR disc only, fluid temperature 0°C to +60°C, no other elastomer can be used.

ASCO™ Solenoid Valves

For High Pressure Fluids | Direct Operated, 1/8" or 1/4" tapped | 15 mm Compression Fittings

**Series
262**

Specifications

Specifications															PRODUCT CODE									
Pipe size	Orifice size	Flow coefficient Kv		Operating pressure differential (bar)								Power coil (W)	Thread type	Dimensions / type ⁽¹⁾	Brass	Stainless steel	Voltage code							
																	24 V/50 Hz	48 V/50 Hz	115 V/50 Hz	230 V/50 Hz	24 V/DC	48 V/DC		
(mm)	(m³/h)	(l/min)	Min.	Max. (PS)						~	=													
				~	=	~	=	~	=	~	=													
Without manual operator																								
NO - Normally open, NBR seal and disc																								
1/8"	1.2	0.05	0.8	0	79	44	62	33	55	22	10.1	11.6	G NPT	02	G262K155S1W00 ⁽²⁾	G262K168S1W00 ⁽²⁾								
					51	44	51	38	51	27	10.1	11.6	G NPT	02	G262K156S1N00	G262K169S1N00								
	2.4	0.18	3	0	18	11	15	9	12	6.5	10.1	11.6	G NPT	02	G262K128S1N00	G262K236S1N00								
															G262K129S1N00	G262K237S1N00								
1/4"	1.2	0.05	0.8	0	79	44	62	33	55	22	10.1	11.6	G NPT	02	E262K161S1W00 ⁽²⁾	E262K199S1W00 ⁽²⁾								
					51	44	51	38	51	27	10.1	11.6	G NPT	02	E262K260S1N00	E262K130S1N00	FL	FR	FT	F8	H1	H9		
	2.4	0.18	3	0	18	11	15	9	12	6.5	10.1	11.6	G NPT	02	E262K261S1N00	E262K134S1N00								
															E262K262S1N00	E262K138S1N00								
	3.2	0.3	5	0	11	6.5	10	6.5	8.5	4.5	10.1	11.6	G NPT	02	E262K263S1N00	E262K142S1N00								
															E262K264S1N00	E262K148S1N00								
	5.6	0.72	12	0	3	2	3	1.7	2.5	1.7	10.1	11.6	G NPT	02	E262K265S1N00	E262K152S1N00								
7.1	0.83	13.8	0	2	1.3	2	1.1	2	1.1	10.1	11.6	G NPT	02		8262K152S1N00									
With maintained manual operator																								
NC - Normally closed, NBR seal and disc																								
1/4"	2.4	0.18	3	0	40	16	28	16	28	15	10.1	11.6	G NPT	02	E262K108S1N01	E262K182S1N01								
					49	41	28	28	27	17.1	22.6	G NPT	02	E262K109S1N01	E262K183S1N01									
	3.2	0.3	5	0	23	7.5	20	7	14	6.5	10.1	11.6	G NPT	02	E262K232S1N01	E262K184S1N01								
					34	17	26	17	24	15	17.1	22.6	G NPT	02	E262K110S1N01	E262K185S1N01								
	4	0.45	7.5	0	14	3.5	13	3.5	10	3.5	10.1	11.6	G NPT	02	E262K202S1N01	E262K220S1N01								
					20	7.5	14	7.5	14	7.5	17.1	22.6	G NPT	02	E262K112S1N01	E262K187S1N01	FL	FR	FT	F8	H1	H9		
	5.6	0.63	10.5	0	6.5	2	6.5	2	6.5	2	10.1	11.6	G NPT	02	E262K208S1N01	E262K226S1N01								
					8.5	4	8.5	4	8.5	4	17.1	22.6	G NPT	02	E262K114S1N01	E262K188S1N01								
	7.1	0.76	12.7	0	4	1.5	5	1.5	4	1.3	10.1	11.6	G NPT	02	E262K210S1N01	E262K189S1N01								
					6	3	6	3	6	3	17.1	22.6	G NPT	02	E262K212S1N01	E262K230S1N01								


⁽¹⁾ For dimensions, see drawing(s) for each construction type on the following page(s).
 (*) Ensure that compatibility of materials in contact with fluids is verified.

⁽²⁾ UR disc only, fluid temperature 0°C to +60°C, no other elastomer can be used.

ASCO™ Solenoid Valves

For High Pressure Fluids | Direct Operated, 1/8" or 1/4" tapped | 15 mm Compression Fittings

Series
262



⁽¹⁾ Check the online configurator for available versions on Emerson.com/ASCO

⁽²⁾ Max. operating pressure limited to 75% of standard value.

⁽³⁾ Search prefix in Emerson.com/ASCO to get detailed technical information.

Please note that the valve pressure ratings with some of the ATEX enclosures will be reduced.


To obtain the correct pressure rating please check the landing pages of the "2-Way Solenoid Valve DIN Configurator".

⁽⁴⁾ Coils class F only.

ASCO™ Solenoid Valves

For High Pressure Fluids | Direct Operated, 1/8" or 1/4" tapped | 15 mm Compression Fittings

Series
262

		Spare parts kits no. (*)																	
		AC (~)									DC (=)								
			NBR	FPM	FPM (oxygen)	EPDM	EPDM (+WRAS)	CR	PTFE	NBR + UR		NBR	FPM	FPM (oxygen)	EPDM	EPDM (+WRAS)	CR	PTFE	NBR + UR
	E262K013/019/020/ 021/022/023/ 090	M200001	N00	V00	VN0	E00	EM0	J00	T00	-	M200005	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K08/109/110/ 112/114	M200007	N00	V00	VN0	E00	EM0	J00	T00	-	M200007	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K130	M200017	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K134	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K138/142/ 148/152	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200034	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K161	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	E262K182/183/184/ 185/187/188/ 189	M200008	N00	V00	VN0	E00	EM0	J00	-	-	M200008	N00	V00	VN0	E00	EM0	J00	-	-
	E262K200	M200007	-	-	-	-	-	-	-	W00	M200007	-	-	-	-	-	-	-	W00
	E262K202/208/ 210/212	M200007	N00	V00	VN0	E00	EM0	J00	T00	-	M200007	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K214	M200008	-	-	-	-	-	-	-	W00	M200008	-	-	-	-	-	-	-	W00
	E262K220/226/230	M200008	N00	V00	VN0	E00	EM0	J00	-	-	M200008	N00	V00	VN0	E00	EM0	J00	-	-
	E262K232	M200007	N00	V00	VN0	E00	EM0	J00	T00	-	M200007	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K260	M200015	N00	V00	VN0	E00	EM0	J00	T00	-	M200031	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K261	M200016	N00	V00	VN0	E00	EM0	J00	T00	-	M200031	-	-	-	-	-	-	-	W00
	E262K262/263/ 264/265	M200016	N00	V00	VN0	E00	EM0	J00	T00	-	M200032	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K001/002/ 014/016	M200001	N00	V00	VN0	E00	EM0	J00	T00	-	M200005	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K128	M200016	N00	V00	VN0	E00	EM0	J00	T00	-	M200031	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K129	M200016	N00	V00	VN0	E00	EM0	J00	T00	-	M200032	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K155	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	G262K156	M200015	N00	V00	VN0	E00	EM0	J00	T00	-	M200031	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K168	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	G262K169	M200017	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K199	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	G262K236	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K237	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200034	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K006/007/012/ 015/036/038	M200003	N00	V00	VN0	E00	EM0	J00	T00	-	M200005	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K080/086	M200003	N00	V00	VN0	E00	EM0	J00	T00	-	M200005	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K130	M200017	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K134	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K138/142/ 148/152	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200034	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K168	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	8262K169	M200017	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K182/183/184/ 185/187/188/ 189	M200008	N00	V00	VN0	E00	EM0	J00	-	-	M200008	N00	V00	VN0	E00	EM0	J00	-	-
	8262K199	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	8262K220/226/230	M200008	N00	V00	VN0	E00	EM0	J00	-	-	M200008	N00	V00	VN0	E00	EM0	J00	-	-
	8262K236	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K237	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200034	N00	V00	VN0	E00	EM0	J00	T00	-

(*) Ensure that compatibility of materials in contact with fluids is verified.

ASCO™ Solenoid Valves

For High Pressure Fluids | Direct Operated, 1/8" or 1/4" tapped | 15 mm Compression Fittings

**Series
262**

Magnetic latching version

Fluids (*)	Temperature range (TS)	Seal materials (*)
water	0°C to +85°C	EPDM

Electrical characteristics

Coil insulation class

F (DC)

Standard voltages

DC (=) : 3V - 6V - 9V - 12V

Operator ambient temperature range (TS)	Power ratings		Replacement coil ⁽¹⁾	
	Hot/cold =		=	
	(W)			
(°C)	640	641/642/643/644	6 V DC	12 V DC
0 to +40	2.5	-	400927-003	400927-005
	-	6	400927-007	400927-014

⁽¹⁾ All coils 400 series are not UL and CSA approved.




Specifications

Specifications									PRODUCT CODE					
Pipe size	Orifice size	Flow coefficient Kv		Operating pressure differential (bar)		Power coil (W)	Thread type	Dimensions / type ⁽²⁾	Brass		Voltage code			
				Min.	Max. (PS)						3 V/DC	6 V/DC	9 V/DC	12 V/DC
	Water (*)													
	(mm)	(m³/h) (l/min)	=		=									
Without manual operator														
EPDM seal and disc														
15 mm compression fittings	1.2	0.05	0.8	0	10	2.5	H	03	H262K640S1EM0	CD	E7	E8	F3	F1
	2.0	0.15	2.5	0	10	6	H	03	H262K641S1EM0					
	3.2	0.30	5.0	0	3	6	H	03	H262K642S1EM0					
	4	0.45	7.5	0	2	6	H	03	H262K643S1EM0					
	6.7	0.82	13.7	0	0.7	6	H	03	H262K644S1EM0					

⁽²⁾ For dimensions, see drawing(s) for each construction type on the following page(s).

(*) Ensure that compatibility of materials in contact with fluids is verified.




(*) Ensure that compatibility of materials in contact with fluids is verified.

ASCO™ Solenoid Valves

For High Pressure Fluids | Direct Operated, 1/8" or 1/4" tapped | 15 mm Compression Fittings

**Series
262**

Accessories code		
	Mounting bracket Steel version (AISI 1010 / 1.1121)	M200094A00
	Mounting bracket Stainless steel version (AISI 304 / 1.4301)	M200095A00

Installation

- The solenoid valves can be mounted in any position without affecting operation
- Solenoid valves have 2 mounting holes in body
- Thread connection "E" applicable for 1/4" have standard thread according to ISO 228/1 and ISO 7/1.
- Thread connection "G" applicable for 1/8", have standard thread according to ISO 228/1
- Thread connection "H" have standard thread = NPT (SAE 71051)
- Thread connection "H" have 1/2" male 'G' thread according to BS 2779 plus cap-nut and olive
- Installation/maintenance instructions are included with each valve

Dimensions (mm), Weight (kg)


Configurator - CAD Files



TYPE 01
Electrical interface "S1"
Epoxy moulded
IEC 335 / ISO 4400
IP65

1/8", power coil 8.1 W / 10.6 W and 11.1 W / 18.6 W

1/4", power coil 8.1 W / 10.6 W and 11.1 W / 18.6 W



Type	Pipe size	A	B	C	D	E	F	G	H	X	Weight ⁽¹⁾
01	1/8"	88	51	30	30	43	62	71	88	26	0.30
	1/4"	88	51	30	40	43	65	75	92	30	0.42

⁽¹⁾ Incl. coil(s) and connector(s).

- ① 2 mounting holes:
M5 dia., depth 6.5 mm (1/8)
M5 dia., depth 7.5 mm (1/4)
- ② Manual operator location

ASCO™ Solenoid Valves

For High Pressure Fluids | Direct Operated, 1/8" or 1/4" tapped | 15 mm Compression Fittings

Series
262

Dimensions (mm), Weight (kg) 


Configurator - CAD Files



TYPE 02
 Electrical interface "S1"
 Epoxy moulded
 IEC 335 / ISO 4400
 IP65

NC: 1/4", power coil 10.1 W / 11.6 W and 17.1 W / 22.6 W

NO: 1/8"-1/4", power coil 10.1 W / 11.6 W



Type	Pipe size	A	B	C	D	E	F	G	H	J	K	X	Weight ⁽¹⁾
02	1/8" (NO)	96	59	34	30	52	67	75	88	17.5	15	26	0.50
	1/4" (NC)	95	57	33	40	50	69	78	96	22	22	30	0.60
	1/4" (NO)	96	59	34	40	52	69	78	96	22	22	30	0.62

⁽¹⁾ Incl. coil(s) and connector(s).

- ① 2 mounting holes: M5 dia., depth 7.5 mm (1/4")
- ② Manual operator location.

ASCO™ Solenoid Valves

For High Pressure Fluids | Direct Operated, 1/8" or 1/4" tapped | 15 mm Compression Fittings

**Series
262**





Dimensions (mm), Weight (kg) 



TYPE 03

Electrical interface "S1"
Epoxy moulded
IEC 335 / ISO 4400
IP65

Magnetic latching coil 2.5 W / 6 W



Magnetic Latching version

① 2 mounting holes:
190-24 UNC-2B, depth 6 mm

Weight ⁽¹⁾

0.45


⁽¹⁾ Incl. coil(s) and connector(s).



Mounting bracket

Steel or stainless steel

M200094A00 / M200095A00



Availability, design and specifications are subject to change without notice.
© 2023 Emerson Electric Co. All rights reserved.