

2/2-way solenoid valve

2/2-way type

Art. No. 148587

Type No. MVB.ES.230V.G12.0,5-12B



Exemplary illustration

The standard series in the versions

- directly operated

- pilot operated

Cable plug in acc. with ISO 4400

Medium temperature max. 130 °C

Technical data

Thread	G 1/2 IT
Operating pressure	0.5 - 12 bar
Voltage	230 V AC
Housing	stainless steel 1.4401
Valve seat	stainless steel
Internal parts	stainless steel
Sealant	EPDM
Medium temperature	-10 to 130 °C
Ambient temperature	-10 to 60 °C
Type	4
Protection IP	IP 65
Electrical connection	ISO 4400 / EN 175301-803 type A
Standard thread	DIN EN ISO 228-1
Opening	12.5 mm
A	82.0 mm
B	79.0 mm
C	52.0 mm

Commercial data

Customs tariff number	84812090
Country of origin	TR
eCl@ss 5.1.4	27220601
eCl@ss 9.0	27220601
UNSPSC_Code_v190501	40141605
UNSPSC_CodeDesc_v190501	Solenoid valves

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
16.04.2026 The specified data do not represent legally guaranteed properties.

Subject to technical changes and errors reserved.
The proficiency testing is the responsibility of the user.
16.04.2026 The specified data do not represent legally guaranteed properties.