

Blow gun

die-cast aluminium nickel-plated

EASY

Art. No. 114321

Type No. 22 B



Exemplary illustration

Standard type.

For blowing out and cleaning machines, workpieces, bore holes, hollow parts, etc.

Technical data

Temperature range	-10 to 50 °C
Working pressure	2 - 6 bar
Max. operating pressure	10 bar
Nozzle	M12x1.25
Nozzle type	standard nozzle, bore 1.5 mm
Extension	M12x1.25
Material	nickel-plated die-cast aluminium
Material push pin	steel 2Cr13
Type of connection	stem I.D. 9
Connecting thread	G 1/4
Air consumption	250 l/min at 6 bar

Commercial data

Customs tariff number	84242000
Country of origin	TW
eCl@ss 5.1.4	21060801
eCl@ss 9.0	21060801
UNSPSC_Code_v190501	27131502
UNSPSC_CodeDesc_v190501	Compressed air gun

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

Accessories

	Art. No.	Type No.
Blow gun holder for aluminium and plastic blow guns, incl. 2 brackets for 90°- or 45°- fixation, incl. screws	142249	BPH-1
Thread adapter, Aluminium, ET M12x1.25, IT G 1/4, Length 26 mm	133178	22.14

Spareparts

	Art. No.	Type No.
Standard nozzle, Hole Ø 1.5 mm, Connection M12x1,25, for all air guns made of aluminium / nickel-plated die-cast aluminium	114344	105/5