

# Constant pressure regulator

EASY

Art. No. 147497

Type No. DRK.G12.BG2.0,5-25B




no image available



keine Abb. vorhanden



no image available



Exemplary illustration

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design.

The pressure regulators maintain a constant working pressure regardless of variations in the inlet pressure.

Note: Technical specifications such as pressure range refer to operation with clean, dry compressed air that is free of chemical additives.

## Technical data

Medium temperature	-10 to 60 °C
Ambient temperature	-10 to 60 °C
Sealant	NBR
grease used	Berulub OX 100 EP
Flow rate measurement	at $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Thread	G 1/2
Size	2
Max. input pressure	40 bar
Housing	die-cast zinc
Control range	0,5 - 25 bar
Flow rate	2200 l/min
A	70.0 mm
B	153.0 mm
C	34.0 mm
D	119.0 mm

## Commercial data

Customs tariff number	84811099
Country of origin	DE
eCl@ss 5.1.4	37011108
eCl@ss 9.0	37011108
UNSPSC_Code_v190501	41112423
UNSPSC_CodeDesc_v190501	Pressure regulator

## Accessories

	Art. No.	Type No.
Mounting bracket with nut and washer, »Standard«, size 1 and size 2, to G 1/2	148646	H 89

## Spareparts

	Art. No.	Type No.
Wear part set for constant pressure regulator, size 2, suitable for control range max. 25 bar	147535	VTSDRK.BG2.25B
Standard pressure gauge, Single scale bar, Connection, rear, centric, G 1/4, Goods class 2.5, Measurement range 0 - 40 bar, Ø 50	101744	209-K