


For the safe and tight assembly of compressed air tube.

Working pressure -0,95 - 15 bar  
Medium Air  
Operating temperature -10 °C to 70 °C

### For special PVC pneumatic hose, aluminium/plastic

Art. No.	Type No.	Thread	for PVC hose	Material	a/f mm	a/f 1 mm	L mm	L1 mm	L2 mm
152978	11.0413/0-1	G 1/8	4x6.2	Aluminium / Plastic	14	13	24.0	13.0	6.5
152979	11.0414/1-1	G 1/8	6x8.2	Aluminium / Plastic	14	15	25.0	14.0	6.5
152981	11.0416/1-1	G 1/4	4x6.2	Aluminium / Plastic	17	13	27.0	13.0	9.0
152982	11.0417/1-1	G 1/4	6x8.2	Aluminium / Plastic	17	15	28.0	14.0	9.0
152983	11.0418/1-1	G 1/4	8x10.2	Aluminium / Plastic	17	16	30.0	16.0	9.0
152984	11.0419/1-1	G 1/4	9x11.6	Aluminium / Plastic	17	19	31.0	17.0	9.0
152985	11.0420/1-1	G 3/8	6x8.2	Aluminium / Plastic	19	15	29.0	14.0	9.0
152986	11.0421/0-1	G 3/8	8x10.2	Aluminium / Plastic	19	16	31.0	16.0	9.0
152992	11.0421/1-1	G 3/8	9x11.6	Aluminium / Plastic	19	19	32.0	17.0	9.0
152987	11.0421/2-1	G 3/8	10x12.5	Aluminium	19	19	34.5	19.5	9.0
152988	11.0421/3-1	G 3/8	13x17.6	Aluminium	22	24	36.0	21.0	9.0
152989	11.0425/0-1	G 1/2	8x10.2	Aluminium / Plastic	24	16	33.0	16.0	11.0
152990	11.0425/1-1	G 1/2	10x12.5	Aluminium	24	19	36.5	19.5	11.0
152991	11.0425/2-1	G 1/2	13x17.6	Aluminium	24	24	38.0	21.0	11.0



11.0421/2-1

### Connection thread, cylindrical - torque for fittings with flat seal rings

Thread	Torque max. plastic seal rings (Nm)	Torque max. Al-, VS- seal rings (Nm)
G 1/8	9	11
G 1/4	18	21
G 3/8	25	28
G 1/2	34	48